

# TECHNICAL DATA SHEET

# DYNAMAX ATF SYSTEM CLEANER

Date issued: 05.05.2016

### **<u>1. Description</u>**

DYNAMAX ATF SYSTEM CLEANER – is a high performance cleaner for automatic gear boxes with and without torque converter. Suitable for all types of automatic transmissions with 4, 5, 6 or 7 gears, continuously variable automatic transmissions, dual clutch transmissions and direct shift gear transmissions.

#### **Application:**

1) Add to automatic gear box before exchanging the transmission fluid.

2) Run engine approx. 15 min with frequent load changes (use all gear positions).

3) Exchange transmission fluid and filter according to manufacture's instructions.

300 ml sufficient for 8 l capacity. For larger capacities add 40 ml per liter of gear oil.

#### **Benefits:**

Removes operationally caused contamination and deposits from the automatic transmission gear box. Protects from corrosion and early wear. Ensures soft shifting with direct response and smooth engine running.

#### Application field: all automatic transmissions

**Consumption:** 300 ml for 8 l gear oil // or 40 ml per 1 liter **Application interval:** with every gear oil change

## **<u>2. Technical parameters</u>**

DYNAMAX ATF SYSTEM CLEANER must comply with the following specifications:

| Physical state                         | liquid         |
|--|----------------|
| Colour                                 | yellow-brown   |
| Odour                                  | charakteristic |
| Relative density [g.cm <sup>-3</sup> ] | 0,814          |
| Boiling Point [°C]                     | 180 - 250      |
| Flash Point [°C]                       | >65            |

Specification variations in these characteristics may occur. Further informations to be available by SDS.