



TECHNICAL DATA SHEET

DYNAMAX CERAMIC OIL ADDITIV

Date issued: 04.05.2016

1. Description

DYNAMAX CERAMIC OIL ADDITIV – highly effective additive packet with wear and tear resistant ceramic for reduced friction and improved wear protection. Compatible with all mineral and synthetic engine oils.

Application:

Add to the warm engine oil after every oil change. 300 ml sufficient to treat 6 l of engine oil. For larger volumes add 50 ml per litre engine oil. Product works during operation. After a mileage of 400-600 km the product reaches its optimum performance level.

Attention: Check engine oil level before application!

Benefits:

Easy to use. Reduced wear and tear due to the creation of a stable wear protection layer. Less running noise, reduced friction and wear ensure increased engine performance and optimized fuel consumption. Reduces exhaust gas emissions.

Application field: all petrol and diesel engines

Consumption: 300 ml for 6 l oil // 50 ml for 1 l

Application interval: with every oil change

2. Technical parameters

DYNAMAX CERAMIC OIL ADDITIV must comply with the following specifications:

Physical state	oil
Colour	white
Odour	characteristic
Relative density [g.cm⁻³]	0,900
Pour Point [°C]	< -39
Flash Point [°C]	> 220

Specification variations in these characteristics may occur. Further informations to be available by SDS.