



TECHNICAL DATA SHEET

DYNAMAX DPF CLEANER

Date issued: 06.05.2016

1. Description

DYNAMAX DPF CLEANER – is a high-performance additive for use in all diesel aggregates to reduce soot and exhaust gas emissions and to increase engine performance. Compatible with all diesel engines and suitable for all kind of diesel fuels.

Application:

Add regularly every 5 000 km right before filling up the tank. Sufficient for 60 l of diesel fuel. Product works during operation.

Benefits:

Only a clean fuel system guarantees optimal operation of all system components, an efficient engine performance and minimum exhaust emissions! Protects the diesel particulate filter and the environment. Reduces soot formation and supports the regeneration of the diesel particulate filter. Enhances storage and corrosion stability of the diesel fuel and acts as defoaming agent. Increases cold start properties. Regular use helps to keep the filter clean and avoids expensive repair works.

Application field: all diesel particulate filters

Consumption: 300 ml for 60 l petrol // resp. 0,5% of the filling content

Application interval: every 5 000 km

2. Technical parameters

DYNAMAX DPF CLEANER must comply with the following specifications:

Physical state	liquid
Colour	yellow-gold
Odour	characteristic
Relative density [g.cm⁻³]	0,810
Boiling Point [°C]	180 - 280
Flash Point [°C]	>78

Specification variations in these characteristics may occur. Further informations to be available by SDS.