

TECHNICAL DATA SHEET

DYNAMAX DPF CLEANING LIQUID

Date issued: 05.05.2016

1. Description

DYNAMAX DPF CLEANING LIQUID – is a highly efficient additive combination for cleaning of dismantled diesel particulate filters. Dissolves contamination in the diesel particulate filter and regenerates its full functionality.

Application:

- 1) Demount the particulate filter and fill in the cleaning liquid approx. 3 to 5 litres depending on the filter size.
- 2) Let the product take effect for approx. 8 to 10 hours.
- 3) Check filling level regularly and refill if necessary.
- 4) Empty particulate filter.
- 5) Thoroughly rinse the filter with clear water after the cleaning process.
- 6) Reassemble the diesel particulate filter and do a test drive for at least 15 min.

Application ratio 1:4 with water (1 l sufficient for 4 l cleaning liquid), in case of strong contamination use 1:1 ratio. Suitable for all diesel particulate filters.

Benefits:

Cleans the diesel particulate filter. Dissolves all operationally caused residues and contamination. Readily biodegradable. Provides a clear cost benefit compared to installation of a new diesel particulate filter.

Application field: all diesel particulate filters **Consumption:** depending on filter size **Application interval:** on demand

2. Technical parameters

DYNAMAX DPF CLEANING LIQUID must comply with the following specifications:

Physical state	liquid
Colour	colourless
Odour	characteristic
Relative density [g.cm ⁻³]	1,068
Boiling Point [°C]	100
Flash Point [°C]	>100

Specification variations in these characteristics may occur. Further informations to be available by SDS.