



TECHNICAL DATA SHEET

DYNAMAX DIESEL BACTERICIDE

Date issued: 06.05.2016

1. Description

DYNAMAX DIESEL BACTERICIDE – is suitable for use in all diesel aggregates and diesel storage tanks. High-performance concentrate with a wide action spectrum for preventive use against bacteria, fungi and yeasts.

Application:

Add regularly every 4 to 6 months to the fuel tank at a ratio of 1:1000 (150 ml sufficient for 150 l fuel). Especially recommended for use in storage tanks, in boats and diesel aggregates that are out of service for a longer period (e.g. motor caravans, construction machines, other commercial vehicles).

Benefits:

Only a clean fuel system guarantees optimal operation of all system components, a clean and powerful combustion and efficient engine performance! Preventively disinfects the complete diesel system. Reliably stops formation of bacteria, fungi and yeast. Existing germs are quickly killed. Regular use helps to prevent new bacterial growth.

Application field: all diesel systems and tanks

Consumption: 150 ml for 150 l diesel // concentrate 1:1000

Application interval: every 4-6 months

2. Technical parameters

DYNAMAX DIESEL BACTERICIDE must comply with the following specifications:

Physical state	liquid
Colour	colourless
Odour	acid
Relative density [g.cm⁻³]	0,841
Boiling Point [°C]	180 - 290
Flash Point [°C]	>67

Specification variations in these characteristics may occur. Further informations to be available by SDS.