



## TECHNICAL DATA SHEET

# DYNAMAX ENGINE CARE & PROTECT

Date issued: 04.05.2016

### 1. Description

DYNAMAX ENGINE CARE & PROTECT – contains a highly effective additive package for increased wear and tear protection properties of all types of engine oils.

#### Application:

Add to the warm engine oil after every oil change. Works during operation. One can (300 ml) sufficient to treat 5 L of engine oil. For larger volumes add 60 ml per litre engine oil. Compatible with all mineral and synthetic engine oils.

Attention: Check engine oil level before application!

#### Benefits:

Only optimal lubrication guarantees minimum wear and tear as well as a long life span of the engine and aggregates! Easy to use. Reduces friction and prevents from wear and tear. Increases the operational reliability at high temperatures. Protects against oil dilution caused by fuel especially in case of frequent short distance travels.

**Application field:** all petrol and diesel engines

**Consumption:** 300 ml for 5 l oil // 60 ml for 1 l

**Application interval:** with every oil change

### 2. Technical parameters

DYNAMAX ENGINE CARE & PROTECT must comply with the following specifications:

<b>Physical state</b>	oil
<b>Colour</b>	yellow-tan
<b>Odour</b>	characteristic
<b>Relative density [g.cm<sup>-3</sup>]</b>	0,900
<b>Pour Point [°C]</b>	< -33
<b>Flash Point [°C]</b>	> 210

Specification variations in these characteristics may occur. Further informations to be available by SDS.