



TECHNICAL DATA SHEET

DYNAMAX GASOLINE SYSTEM CLEAN & PROTECT

Date issued: 04.05.2016

1. Description

DYNAMAX GASOLINE SYSTEM CLEAN & PROTECT – ensures effective cleaning of the entire fuel system from the tank to the combustion chamber. Removes operationally caused contamination and prevents formation of new deposits.

Application:

Add every 6 months to the fuel tank before filling up. Recommended for all petrol engines. Especially in case of cold start problems or bad exhaust values. Treats 60 l of petrol. For larger tank volumes add 0,5% of the filling content. Product works during operation.

Attention: Cleaning fluid – not a fuel substitute!

Benefits:

Only a clean fuel system guarantees clean and powerful combustion and efficient engine performance! Easy application without extra effort. Reduces the fuel consumption and optimizes the exhaust gas emission values. Protects from corrosion and increases the operational reliability.

Application field: all petrol engines

Consumption: 300 ml for 60 l petrol // resp. 0,5% of the filling content

Application interval: every 6 months

2. Technical parameters

DYNAMAX GASOLINE SYSTEM CLEAN & PROTECT must comply with the following specifications:

Physical state	liquid
Colour	red
Odour	characteristic
Boiling Point [°C]	35
Flash Point [°C]	2

Specification variations in these characteristics may occur. Further informations to be available by SDS.