



TECHNICAL DATA SHEET

DYNAMAX HYDRAULIC LIFTER CARE

Date issued: 09.05.2016

1. Description

DYNAMAX HYDRAULIC LIFTER CARE – reduces damage to hydraulic lifters in the mutual friction, reduces wear and noise produced by lifters. It cleans valves and openings in the hydraulic lifter and thereby promotes optimum performance and improves cold start.

Application:

The product DYNAMAX HYDRAULIC LIFTER CARE can be used to adjust the engine oil for all gasoline and diesel engines. Before use, it is advisable to clean the oil system preparation Dynamax Oil System Cleaner. After cleaning, pour new oil with the addition DYNAMAX HYDRAULIC LIFTER CARE.

Dosing: 300 ml of the preparation of 6 liters oil.

Application field: all petrol and diesel engines

Consumption: 300 ml for 6 l oil // 50 ml for 1 l

Application interval: with every oil change

2. Technical parameters

DYNAMAX HYDRAULIC LIFTER CARE must comply with the following specifications:

Physical state	liquid
Colour	colourless
Odour	characteristic
Relative density [g.cm⁻³]	0,850
Freezing Point [°C]	- 39
Flash Point [°C]	>220

Specification variations in these characteristics may occur. Further informations to be available by SDS.