



TECHNICAL DATA SHEET

DYNAMAX RADIATOR STOP LEAK

Date issued: 05.05.2016

1. Description

DYNAMAX RADIATOR STOP LEAK – for use in all water-cooled, closed cooling systems (commercial vehicles, passenger cars, industrial heat exchangers). Reliably seals critical hairline cracks and small leaks - quick and easy. Also for preventive usage.

Application:

- 1) Check the coolant level.
 - 2) Add the product to the warm cooling system. Move all heater controls to “hot”.
 - 3) Let the engine idle for approx. 10 minutes.
 - 4) Check the coolant level again and test if the sealing was successful.
- Attention: Open radiator filling port slowly and successively - risk of burning!
300 ml sufficient for cooling systems of 12 l capacity. For larger volumes add 25 ml per litre coolant.

Benefits:

The major part of chemical energy that is bound in the fuel is converted into heat during the combustion process which must be dissipated. Therefore a fully functional cooling system is of major importance for the operational liability of engines! Helps to avoid expensive repair works. Prevents from loss of cooling liquid and protects against engine damage.

Application field: all cooling systems

Consumption: 300 ml for up to 12 l // resp. 25 ml for 1 l coolant

Application interval: add with every filling

2. Technical parameters

DYNAMAX RADIATOR STOP LEAK must comply with the following specifications:

Physical state	liquid
Colour	green-blue
Odour	charakteristic
Relative density [g.cm⁻³]	1,023
Boiling Point [°C]	100
pH	7,2

Specification variations in these characteristics may occur. Further informations to be available by SDS.