

TECHNICAL DATA SHEET DYNAMAX

GOLDLINE FUEL ECO 0W/16

Date issued: 31.05.2024

Motor Oil

1. Product description:

DYNAMAX GOLDLINE FUEL ECO 0W/16 - is a fully synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. It is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

DYNAMAX GOLDLINE FUEL ECO 0W/16 offers:

- Excellent cold starting properties, even at low temperatures
- A very stable and excellent viscosity behaviour and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Excellent protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

Use:

DYNAMAX GOLDLINE FUEL ECO 0W/16 - is an energyefficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. It therefore reduces the CO2 emissions and contributions to the protection of the environment.

Specification:

SAE 0W/16
API SN

Approvals:

-

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	7,2
Kinematic viscosity at 40°C, mm ² /s	typical value	38,6
Viscosity index	min.	153
Density at 15°C, kg/m ³	typical value	843
Pour point, °C	max.	- 63
Flash point (COC), °C	min.	242

Specification variations in these characteristics may occur. Further informations to be available by SDS.