

TECHNICAL DATA SHEET DYNAMAX SN PLUS 10W/40

Date issued: 06.02.2024

1. Product description:

DYNAMAX PREMIUM SN PLUS 10W/40 - is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Use:

DYNAMAX PREMIUM SN PLUS 10W/40 - is an universal high performance fuel saving semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

Specification:

Approvals:

SAE 10W/40 API SN/CF ACEA A3/B4 MB 229.1, 229.3; Renault RN 0700, 0710 PSA B712300, RN700 / RN710

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	14
Kinematic viscosity at 40°C, mm ² /s	typical value	98,5
Viscosity index	min.	148
Density at 15°C, kg/m3	typical value	872
Pour point, °C	max.	- 36
Flash point (COC), °C	min.	215

Specification variations in these characteristics may occur. Further informations to be available by SDS.