



## TECHNICAL DATA SHEET

Date issued: 27.06.2018

# DYNAMAX ATF MB

### 1. Product description:

DYNAMAX ATF MB - is based on special selected high performance synthetic base oil in combination with a special selected EP-additive package to reach to following properties:

- Excellent thermal- and oxidation stability.
- Excellent low temperature properties.
- Good shifting even at low temperatures.
- High viscosity index.
- Excellent shifting even after long use.
- Extended drain interval possible.
- Fuel saving properties.
- Excellent protection against the forming of foam, corrosion and wear.

#### Use:

DYNAMAX ATF MB - is a high-quality fuel saving fully synthetic automatic transmission oil specially developed for the last generation MB (NAG-2) 7-speeds automatic transmissions. DYNAMAX ATF MB is backwards compatible to automatic transmissions where a MB 236.12 specification is recommended.

#### Specification:

-

#### Approvals:

MB 236.14, Ssang-Yong

### 2. Technical parameters:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	typical value	5,6
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	typical value	26,6
Viscosity index	min.	159
Density at 15°C, kg/m <sup>3</sup>	typical value	843
Pour point, °C	max.	- 48
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.