



TECHNICAL DATA SHEET

Date issued: 30.09.2016

DYNAMAX AUTOMATIC ATF VI

1. Product description:

DYNAMAX AUTOMATIC ATF VI is a supreme performance long life automatic transmission fluid specially developed for all 2006 and beyond General Motors vehicles equipped with Hydramatic automatic transmissions. DYNAMAX AUTOMATIC ATF VI is also recommended for automatic transmission of passenger cars and light vans requiring DEXRON® III(G&H), DEXRON® IID and DEXRON® IIE fluids.

DYNAMAX AUTOMATIC ATF VI is based on exceptional quality synthetic base oil in combination with a special selected EP-additive package to reach to following properties:

- good thermo-and oxidation
- controlled frictional characteristics for a smooth shifts in a variety of driving conditions
- extended drain interval possible
- excellent antiwear, antirust and anticorrosion technology
- high Viscosity index ensures adequate lubrication in both high operating & low starting temperatures
- better foam control leads to smooth & lasting shift feel and reduces fluid loss
- enhanced Low temperature fluidity assist in good cold start performance
- compatibility with all common seal materials

Specification:

DEXRON® VI

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	6,1
Kinematic viscosity at 40°C, mm ² /s	typical value	29,9
Viscosity index	min.	150
Density at 15°C, kg/m ³	typical value	842
Pour point, °C	max.	-48
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.