



TECHNICAL DATA SHEET

Date issued: 15.01.2016

DYNAMAX COOL G11

1. Product description:

DYNAMAX COOL G11 is a concentrate of low solidifying liquid cooling systems based on ethylene glycol. It is designed to coolers for the engine alloy. DYNAMAX COOL G11 protects the car year-round cooling system from the action of frost and corrosion. It provides very good heat transfer. Includes high-inhibitors corrosion protection for cooling system. Meets VW TL 774 C.

Use:

DYNAMAX COOL G11 is used for cooling systems for internal combustion engines. DYNAMAX COOL G11 serves as a full replacement for the coolant, which are made based on 1,2 - ethylene glycol (or glycol). DYNAMAX COOL G11 may be diluted to desired temperature with distilled water or drinking water quality. Compatible with metal materials.

Painted surfaces should be sprayed with water after.

DYNAMAX COOL G11 is used after dilution in the following table.

Table dilution:

Freezing point in °C	Volume of water	Volume parts DYNAMAX COOL G11
-32	1	1
-26	1,5	1
-17	2	1

Temperature tolerance is $\pm 2^{\circ}\text{C}$.



TECHNICAL DATA SHEET

2. Technical parameters:

Physical state	liquid
Colour	blue
Odour	odorless
Freezing point, °C	- 32 (mixed with water 1:1)
Density at 20°C, kg/m ³	1,110 - 1,140
Solubility in water, g.l ⁻¹	soluble
Solubility in solvents, g.l ⁻¹	alcohol, ether

Specification variations in these characteristics may occur. Further informations to be available by SDS.