



TECHNICAL DATA SHEET

Date issued: 26.06.2018

DYNAMAX GOLDLINE FS 0W/40

1. Product description:

DYNAMAX GOLDLINE FS 0W/40 - is a fully synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. It is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

DYNAMAX GOLDLINE FS 0W/40 offers:

- Excellent cold starting properties, even at low temperatures below -35°
- A very stable and excellent viscosity behaviour and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Excellent protection against wear, corrosion and foaming
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

Use:

DYNAMAX GOLDLINE FS 0W/40 - is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

Specification:

SAE 0W/40
API SN, ACEA A3/B4

Approvals:

VW 502.00/505.00, BMW Longlife-01
Porsche A40, RN700 / RN710

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	13,7
Kinematic viscosity at 40°C, mm ² /s	typical value	74,5
Viscosity index	min.	179
Density at 15°C, kg/m ³	typical value	883
Pour point, °C	max.	- 46
Flash point (COC), °C	min.	226

Specification variations in these characteristics may occur. Further informations to be available by SDS.