



## TECHNICAL DATA SHEET

Date issued: 19.11.2015

# DYNAMAX GOLDLINE LONGLIFE 0W/30

### 1. Product description:

DYNAMAX GOLDLINE LONGLIFE 0W/30 - is a fully synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. It is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

DYNAMAX GOLDLINE LONGLIFE 0W/30 offers:

- Excellent cold starting properties, even at low temperatures below -30°C
- A very stable and excellent viscosity behaviour and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Excellent protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

#### Use:

DYNAMAX GOLDLINE LONGLIFE 0W/30 - is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

#### Specification:

**SAE 0W/30**

ACEA A5/B5

API SL

#### Approvals:

VW 503.00/506.00/506.01

### 2. Technical parameters:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	typical value	10
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	typical value	53,5
Viscosity index	min.	170
Density at 15°C, kg/m <sup>3</sup>	typical value	846
Pour point, °C	max.	- 45
Flash point (COC), °C	min.	231

Specification variations in these characteristics may occur. Further informations to be available by SDS.