



## TECHNICAL DATA SHEET

Date issued: 28.06.2018

### DYNAMAX HYPOL 75W/80 GL-5

#### **1. Product description:**

DYNAMAX HYPOL 75W/80 - is based on high quality synthetic base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including latest carbon.
- Good frictional properties provide improved fuel economy and smoother shift ability

#### Use:

DYNAMAX HYPOL 75W/80 - is a high quality fuel saving synthetic thermally stable long life gear lubricant designed for passenger- and commercial vehicles using manual transmissions fitted with different synchronizers including latest ones based on carbon.

#### Specification:

**API GL-4**

#### Approvals:

MB 235.4, Volvo 97305, MAN 341 E3, MAN 341 Z4  
Iveco, Renault B0032/2, Eaton Europe, ZF TE-ML 01L, 02L, 08, 16K

#### **2. Technical parameters:**

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	typical value	9,8
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	typical value	58,5
Viscosity index	min.	155
Density at 15°C, kg/m <sup>3</sup>	typical value	862
Pour point, °C	max.	- 39
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.