



TECHNICAL DATA SHEET

Date issued: 17.08.2021

DYNAMAX HYPOL 75W-90 GL-5

1. Product description:

DYNAMAX HYPOL 75W-90, GL-5 is universal, synthetic oil for vehicle gears. It is intended for gears, in particular for hypoid gears of cars, trucks, buses and of other vehicles, machines and devices operating in very difficult conditions, where manufacturer recommends API GL-5 oils.

Specification: **SAE 75W-90** API GL-5

Approvals:

- MIL-L 2105D/MIL-PRF-2105E
- MB 235.8, MB 235.0/235.72
- MAN 341 Typ E3/3343 Typ S/342 Typ M3/S1, MAN 341 Typ Z2/342 Typ M2
- ZF TE-ML 02B,05B, 07A,08,12B,12L,12N 16F,17B,19C,21B 05A,12E,16B,19B,21A
- Volvo 97312, Ford SQM-2C-9002 AA/M2C200-C; GM 1940182/1940768/M75/1
- VW G 50/51 (VW 501.50/51)/G052 190/G052 911; MF 1134;
- Scania STO 1:0/STO 2:0A FS

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	15,5
Kinematic viscosity at 40°C, mm ² /s	typical value	78,5
Viscosity index	min.	210
Density at 15°C, kg/m ³		845-870
Pour point, °C	max.	- 44
Flash point (COC), °C	min.	192

Specification variations in these characteristics may occur. Further informations to be available by SDS.