



## TECHNICAL DATA SHEET

Date issued: 14.10.2017

### DYNAMAX HYPOL 80W-90 GL-5

#### 1. Product description:

DYNAMAX HYPOL 80W-90 GL-5 is vehicle gear mineral oil with very good lubricating, antioxidative, anticorrosive and antifoaming properties.

DYNAMAX HYPOL 80W-90 GL-5 is mineral oil intended to lubricate gears of vehicles operating in very difficult conditions, especially for gearboxes and final drives, where API GL-5 oil is recommended, it is featured by perfect properties guaranteeing maximal protection against mechanical wear out. It can be used for the lubrication of mechanical gearboxes and final drives of modern passenger vehicles and trucks, construction mechanisms, agricultural machines and other transmission applications.

#### Specification:

**SAE 80W-90**  
API GL-5

#### Approvals:

MIL-L 2105D  
Autosan S. A., Eaton Truck Components S.A.

#### 2. Technical parameters:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	typical value	14,5
Viscosity index	min.	99
Density at 15°C, kg/m <sup>3</sup>	typical value	880
Pour point, °C	max.	- 20
Flash point (COC), °C	min.	190

Specification variations in these characteristics may occur. Further informations to be available by SDS.