



TECHNICAL DATA SHEET

Date issued: 28.06.2018

DYNAMAX HYPOL 85W/140 GL-5

1. Product description:

DYNAMAX HYPOL 85W/140 - is based on high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good Extreme Pressure and Antiwear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

Use:

DYNAMAX HYPOL 85W/140 - is a high performance gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives.

Specification:

API GL-5

Approvals:

MIL-L-2105D, MAN 342 M2
ZF TE-ML 05A, 07A, 12E, 16B/C/D, 17B, 19B, 21A

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	28,4
Kinematic viscosity at 40°C, mm ² /s	typical value	395
Viscosity index	min.	99
Density at 15°C, kg/m ³	typical value	906
Pour point, °C	max.	- 12
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.