



TECHNICAL DATA SHEET

Date issued: 09.03.2015

DYNAMAX MOTOFORCE 2T SUPER SCOOTER

1. Product description:

DYNAMAX MOTOFORCE 2T SUPER SCOOTER is a high quality lubricant suitable for use in air-cooled two-stroke gasoline engines operating under severe conditions. It consists of highly refined base ingredients fortified with carefully selected additives to ensure the protection and engine cleanliness. Offers great lubrication that protects against piston abrasion and premature wear of engine parts. Great miscibility with gasoline ensures a homogeneous mixture even at low ambient temperatures.

Use:

DYNAMAX MOTOFORCE 2T SUPER SCOOTER is recommended for two-stroke motorcycles and scooters requiring high quality oil API TC or JASO FC and is suitable for both oil injection and lubrication systems with the premixed composition. Recommended mixing from 50:1 to 25:1.

Specification:

SAE 40
API TC, JASO FC

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	10,0 – 12,0
Viscosity index	min.	95
Density at 15°C, kg/m ³	typical value	872
Pour point, °C	max.	- 21
Flash point (COC), °C	min.	210

Specification variations in these characteristics may occur. Further informations to be available by SDS.