



TECHNICAL DATA SHEET

Date issued: 24.08.2018

DYNAMAX MOTOFORCE 2T SUPER

1. Product description:

DYNAMAX MOTOFORCE 2T SUPER is based on a high quality virgin and synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Outstanding protection against piston scuffing and premature wear of engine components.
- Excellent control against engine deposits, exhaust system blocking.
- Extended engine life without power loss.
- Low ash additive technology prevents pre-ignition and spark plug fouling.
- Specially selected synthetic base fluid reduces visible exhaust smoke.
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures.

Use:

DYNAMAX MOTOFORCE 2T SUPER is a high quality semi-synthetic lubricant specially developed for high powered 2-stroke air cooled gasoline engines fitted with oil-injection or premix systems.

Specification:

API TC
JASO FD
ISO-L-EGD

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	9,5
Kinematic viscosity at 40°C, mm ² /s	typical value	62,5
Viscosity index	min.	135
Density at 15°C, kg/m ³	typical value	883
Pour point, °C	max.	- 36
Flash point (COC), °C	min.	85

Specification variations in these characteristics may occur. Further informations to be available by SDS.