



## TECHNICAL DATA SHEET

Date issued: 24.08.2018

# DYNAMAX MOTOFORCE 2T SYNTECH

### 1. Product description:

DYNAMAX MOTOFORCE 2T SYNTECH is based on a high quality synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Exceptional protection against piston scuffing and wear of engine components.
- Exceptional control against engine deposits, exhaust system blocking.
- Extended engine life without power loss .
- Specially selected synthetic base fluid reduces visible exhaust smoke .
- Low ash additive technology prevents pre-ignition and spark plug .
- Easy miscibility with gasoline ensure stable homogeneous mixture even at low ambient temperatures.

#### Use:

DYNAMAX MOTOFORCE 2T SYNTECH is a supreme performance synthetic lubricant specially developed for high output air cooled 2-stroke motorcycles and scooters operating under severe conditions

#### Specification:

**API TC**  
**JASO FD**  
**ISO-L-EGD**

### 2. Technical parameters:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	typical value	6,9
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	typical value	33,3
Viscosity index	min.	175
Density at 15°C, kg/m <sup>3</sup>	typical value	883
Pour point, °C	max.	- 54
Flash point (COC), °C	min.	90

Specification variations in these characteristics may occur. Further informations to be available by SDS.