



TECHNICAL DATA SHEET

Date issued: 24.08.2017

DYNAMAX MOTOFORCE 4T SUPER SCOOTER 10W/40

1. Product description:

DYNAMAX MOTOFORCE 4T SUPER SCOOTER 10W40 is a semi-synthetic, 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance air cooled 4-stroke motorcycles. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

Use:

DYNAMAX MOTOFORCE 4T SUPER SCOOTER 10W40 is based on a high quality synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Excellent antiwear, antirust and anticorrosion properties.
- Good thermo-and oxidative.
- Controlled frictional properties eliminate clutch slippage and improves drivability
- Excellent dispersant and detergent properties

Specification:

SAE 10W/40
JASO MA
API SL

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	14,5
Kinematic viscosity at 40°C, mm ² /s	typical value	99
Viscosity index	min.	160
Density at 15°C, kg/m ³	typical value	872
Pour point, °C	max.	- 33
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.