



## TECHNICAL DATA SHEET

Date issued: 24.08.2017

# DYNAMAX MOTOFORCE 4T SYNTECH 10W/40

### 1. Product description:

DYNAMAX MOTOFORCE 4T SYNTECH 10W40 is fully synthetic motor oil of outstanding quality developed for highperformance four-stroke engines synthetic oil recommended for four-stroke engines. Suitable for motorcycles which are compatible with wet clutches. Creates effective lubricating film which provides antiwear protection. Ensures long engine life without its powerloss. High and stable viscosity index guarantees optimum lubrication even in the most demanding conditions.

#### Use:

DYNAMAX MOTOFORCE 4T SYNTECH 10W40 is based on a high quality synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Excellent antiwear, antirust and anticorrosion properties.
- Good thermo-and oxidative.
- Controlled frictional properties eliminate clutch slippage and improves drivability
- Excellent dispersant and detergent properties

#### Specification:

**SAE 10W/40**  
**JASO MA2**

### 2. Technical parameters:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	typical value	14,4
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	typical value	90,5
Viscosity index	min.	165
Density at 15°C, kg/m <sup>3</sup>	typical value	846
Pour point, °C	max.	- 44
Flash point (COC), °C	min.	236

Specification variations in these characteristics may occur. Further informations to be available by SDS.