



TECHNICAL DATA SHEET

Date issued: 28.08.2017

DYNAMAX MOTOFORCE 4T SYNTECH SCOOTER 5W/40

1. Product description:

DYNAMAX MOTOFORCE 4T SYNTECH SCOOTER 5W40 is a 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance air cooled 4-stroke motorcycles. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

Use:

DYNAMAX MOTOFORCE 4T SYNTECH SCOOTER 5W40 is based on a high quality synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Outstanding thermo-oxidative stability.
- Exceptional antiwear, antirust and anticorrosion properties.
- Controlled frictional properties eliminate clutch slippage.
- Increased power/ fuel economy and improves drivability.
- Excellent dispersancy and detergency properties.
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up.
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution.

Specification:

SAE 5W/40

JASO MA2

API SL

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	13,6
Kinematic viscosity at 40°C, mm ² /s	typical value	82
Viscosity index	min.	171
Density at 15°C, kg/m ³	typical value	839
Pour point, °C	max.	- 45
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.