



TECHNICAL DATA SHEET

Date issued: 25.08.2015

DYNAMAX RACING SL 10W/60

1. Product description:

DYNAMAX RACING SL 10W/60 - is based on high quality 100% synthetic Poly Alpha Olefin (PAO) in combination with an unique additive package to ensure the following properties:

- Excellent thermal and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

Use:

DYNAMAX RACING SL 10W/60 - is a high performance fully synthetic motor oil of exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines in passenger cars with or without turbocharger, working under severe temperatures and load conditions.

Specification:

SAE 10W/60
ACEA A3/B4
API SL/CF

Approvals:

MB 229.1, VW 502.00/505.00

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	24
Kinematic viscosity at 40°C, mm ² /s	typical value	173
Viscosity index	min.	170
Density at 15°C, kg/m ³	typical value	851
Pour point, °C	max.	- 36
Flash point (COC), °C	min.	201
Total Base Number, mgKOH/g	typical value	11,4
Sulphated Ash, % Wt	typical value	1,3

Specification variations in these characteristics may occur. Further informations to be available by SDS.