



TECHNICAL DATA SHEET

Date issued: 29.06.2018

DYNAMAX TRACTOR PLUS 10W/30

1. Product description:

DYNAMAX TRACTOR PLUS 10W/30 - is a high quality universal mineral based so called "Super Tractor Oil Universal" (STOU) designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". is formulated on high refined solvent mineral base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

Use:

DYNAMAX TRACTOR PLUS 10W/30 - is developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. This product cannot be used in diesel engines equipped with a Diesel Particle Filter (DPF).

Specification:

API GL-4
API CG-4/CF-4/CE/SF
ACEA E3

Approvals:

MB 227.1, Ford M2C86B/C, Ford M2C 134D
JD J20C/D, Case MS 1204/6/7/9, MF M 1135/1139
MF M 1143/1145, Cat TO-2, Allison C-4
Eaton M-2950S, Eaton I-280-S, Danfoss

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	10,5
Kinematic viscosity at 40°C, mm ² /s	typical value	67,1
Viscosity index	min.	157
Density at 15°C, kg/m ³	typical value	861
Pour point, °C	max.	- 36
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.