



TECHNICAL DATA SHEET

Date issued: 10.10.2019

DYNAMAX TRACTOR PLUS E 10W/40

1. Product description:

DYNAMAX TRACTOR PLUS E 10W40 is a new generation SHPDO type (Super High Performance Diesel Oil) semi-synthetic motor oil designated for the lubrication of diesel engines with turbo-supercharging and the non-supercharged ones. It has improved properties in terms of piston cleanliness, cylinder surface polishing, reduced wear, soot contamination and resistance against ageing. It meets the emission-related requirements pursuant to Euro 4.

Use:

DYNAMAX TRACTOR PLUS E 10W40 is recommended for diesel engines working under very hard conditions such as prolonged oil change intervals as recommended by engine manufacturers and/or where special quality of oil is required. It is designated particularly for the operation of diesel engines used in heavy trucks, construction mechanisms and busses.

Specification:

SAE 10W/40
ACEA E4/E7, B4
API CI4/CF

Approvals:

MB 228.3/229.1, Volvo VDS-3, Renault VI RLD-2
Mack EO-N, VW 500.00/505.00, MAN M3275
Deutz DQC III-10, Caterpillar TO-2, Mack EO-M Plus
Allison C-4, MTU Typ 2

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	13,7
Kinematic viscosity at 40°C, mm ² /s	typical value	89,1
Viscosity index	min.	151
Density at 15°C, kg/m ³	typical value	868
Pour point, °C	max.	- 36
Flash point (COC), °C	min.	220

Specification variations in these characteristics may occur. Further informations to be available by SDS.