



## TECHNICAL DATA SHEET

Date issued: 15.08.2017

### DYNAMAX TRACTOR PLUS L 15W/40

#### **1. Product description:**

DYNAMAX TRACTOR PLUS L 15W40 is a new generation SHPDO type (Super High Performance Diesel Oil) oil recommended for highly loaded non-supercharged and supercharged diesel engines, featuring improved properties in terms of piston cleanliness, cylinder surface polishing, reduced wear, soot control and resistance against ageing. It enables to achieve very long oil change intervals.

#### Use:

DYNAMAX TRACTOR PLUS L 15W40 is designated particularly for the operation of diesel engines used in heavy trucks, construction mechanisms and busses.

#### Specification:

**SAE 15W/40**  
ACEA E3/E5/E7  
API CI4/CF/SL

#### Approvals:

MB 228.3, MAN M 3275, Volvo VDS-3, TEDOM 258-3  
Tatra TDS 30/12, Renault Trucks RLD-2, MTU Type 2,  
Cummins CES 20078,77,76; Avia, Deutz DQC II-10,  
ZETOR, Caterpillar ECF-1a, MACK E-OM Plus

#### **2. Technical parameters:**

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	typical value	14,0-16,3
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	typical value	113,8
Viscosity index	min.	135
Density at 15°C, kg/m <sup>3</sup>	typical value	885
Pour point, °C	max.	- 30
Flash point (COC), °C	min.	225

Specification variations in these characteristics may occur. Further informations to be available by SDS.