



TECHNICAL DATA SHEET

Date issued: 15.08.2017

DYNAMAX TRACTOR PLUS TX 10W/40

1. Product description:

DYNAMAX TRACTOR PLUS TX 10W40 is high quality Super Tractor Oil Universal, so called STOU oil, has been developed for use in hydraulic system and for lubrication of gearbox, PTO, final drive as well as so called „wet disc brakes“. Provides optimal engine protection of agricultural machinery.

Use:

DYNAMAX TRACTOR PLUS TX 10W40 is designated particularly for the operation of diesel engines used in heavy trucks, construction mechanisms and busses.

Specification:

SAE 10W/40
ACEA E2
API CG4/SF, API GL-4
HVLP D (DIN 51524 Part 3)

Approvals:

MB 227.1, MB 228.1, MB 228.3, John Deere J20C/D, J27
Fendt KDM 41.2011, Massey Ferguson CMS 1145, 1144, 1139
Allison C4, Ford ESN-M2C 134 B/C/D, 159B/C
ZF TE ML 06A, 06B, 06C, 06D, 07B
Caterpillar TO-2, MAN 271, MIL-L-2104D
Case IH-MS 1209, New Holland NH 410B, MAT 3525

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	13
Kinematic viscosity at 40°C, mm ² /s	typical value	88
Viscosity index	min.	152
Density at 15°C, kg/m ³	typical value	869
Pour point, °C	max.	- 36
Flash point (COC), °C	min.	242

Specification variations in these characteristics may occur. Further informations to be available by SDS.