



## TECHNICAL DATA SHEET

Date issued: 15.03.2018

# DYNAMAX TRACTOR PLUS TXM

### 1. Product description:

DYNAMAX TRACTOR PLUS TXM is high quality Universal Tractor Transmission Oil, so-called UTTO oil. Contains additives which protect against wear and extreme pressure (EP). The oil is not suitable for lubrication of the engine!

#### Use:

DYNAMAX TRACTOR PLUS TLV is recommended for use in modern agricultural machinery that require one multiple oil for hydraulic system, gearbox, differential, PTO or so called „wet disc brakes“.

#### Specification:

**SAE 85W**

**API GL-4**

#### Approvals:

John Deere J20C, Ford M2C 134-D

Case NH MAT3525/3526, Massey Ferguson M1135/1143/1145

ZF TE-ML 03E/05E, Volo WB 101

### 2. Technical parameters:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	typical value	11,6
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	typical value	71
Viscosity index	min.	160
Density at 15°C, kg/m <sup>3</sup>	typical value	885
Pour point, °C	max.	- 39
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.