



TECHNICAL DATA SHEET

Date issued: 02.07.2018

DYNAMAX TRUCKMAN HDX 20W/50

1. Product description:

DYNAMAX TRUCKMAN HDX 20W/50 - is formulated with high refined solvent mineral base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

Use:

DYNAMAX TRUCKMAN HDX 20W/50 - is an extra high performance universal engine oil de-signed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

Specification:

API: CI-4
ACEA E7

Approvals:

MB 228.3, MAN M 3275, Volvo VDS-3
Renault RLD-2, MAN EO-N, Allison C-4
DDC 93K215, CAT ECF-1a, ECF-2, Global DHD-1
JASO DH-1, MTU Type 2, DAF HP-2
Cummins CES 20077/20078

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	16,8
Kinematic viscosity at 40°C, mm ² /s	typical value	135
Viscosity index	min.	130
Density at 15°C, kg/m ³	typical value	890
Pour point, °C	max.	- 33
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.