



## TECHNICAL DATA SHEET

Date issued: 02.07.2018

### DYNAMAX TRUCKMAN SUPER 20W/50

#### **1. Product description:**

DYNAMAX TRUCKMAN SUPER 20W/50 - is a mineral engine oil used for lubrication of engines of older vehicles and vehicles that have crossed a number of kilometers.

- good thermal- and oxidation stability
- good dispersancy and detergency
- high anti-foam, anti-wear and anti-corrosion properties

#### Use:

DYNAMAX TRUCKMAN SUPER 20W/50 - is used for lubrication of all diesel engines types with normal and turbo charging, built-in commercial vehicles, which operate under heavy exploitation conditions.

#### Specification:

API CF-4/SG  
ACEA E2

#### Approvals:

MB 228.1; MAN 271; VOLVO VDS

#### **2. Technical parameters:**

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	typical value	18 – 19,5
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	typical value	135
Viscosity index	min.	135
Density at 15°C, kg/m <sup>3</sup>	typical value	878
Pour point, °C	max.	- 24
Flash point (COC), °C	min.	230

Specification variations in these characteristics may occur. Further informations to be available by SDS.