



TECHNICAL DATA SHEET

Date issued: 25.11.2016

DYNAMAX ULTRA F 5W/30

1. Product description:

DYNAMAX ULTRA F 5W/30 - is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- excellent cold starting properties, even at low temperatures
- fuel savings under all operating conditions
- very good detergent and dispersing properties
- neutrality towards sealants
- low evaporation, thus low oil consumption
- extensive protection against wear, corrosion and foaming
- extended oil change intervals protect natural resources

Use:

DYNAMAX ULTRA F 5W/30 - is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. It is an energy-efficient engine oil for year-round use, and is ideal for modern petrol and diesel car engines. It is an engine oil specifically for the requirements of Ford and Renault.

Specification:

SAE 5W/30
ACEA A1/B1, A5/B5
API SL

Approvals:

RN0700, Ford WSS-M2C913-D, Ford WSS-M2C913-C

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	9,5
Kinematic viscosity at 40°C, mm ² /s	typical value	55
Viscosity index	min.	167
Density at 15°C, kg/m ³	typical value	850
Pour point, °C	max.	- 48
Flash point (COC), °C	min.	196

Specification variations in these characteristics may occur. Further informations to be available by SDS.