



TECHNICAL DATA SHEET

Date issued: 20.09.2017

DYNAMAX ULTRA FEB 5W/20

1. Product description:

DYNAMAX ULTRA FEB 5W/20 - is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear.

DYNAMAX ULTRA FEB 5W/20 offers:

- a very stable and excellent viscosity behaviour and shear stability
- fuel savings under all operating conditions
- very good detergent and dispersing properties
- neutrality towards sealants
- extensive protection against wear, corrosion and foaming.
- suitable for catalytic converters
- low evaporation, thus low oil consumption
- extended oil change intervals protect natural resources
- excellent cold starting properties
- lowSAPS = low sulphated ash, phosphorous and sulphur

Use:

DYNAMAX ULTRA FEB 5W/20 - is a synthetic Low SAPS smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection.

Specification:

SAE 5W/20
ACEA A1/B1
API SN

Approvals:

Ford WSS M2C-948B

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	8,4
Kinematic viscosity at 40°C, mm ² /s	typical value	48,5
Viscosity index	min.	163
Density at 15°C, kg/m ³	typical value	855
Pour point, °C	max.	- 39
Flash point (COC), °C	min.	201

Specification variations in these characteristics may occur. Further informations to be available by SDS.