



TECHNICAL DATA SHEET

Date issued: 26.06.2018

DYNAMAX PREMIUM ULTRA LE 5W/30

1. Product description:

DYNAMAX PREMIUM ULTRA LE 5W/30 - is based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.
- Fuel saving properties.

Use:

DYNAMAX PREMIUM ULTRA LE 5W/30 - is a high performance fuel saving MID SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger car and light vans with or without turbocharger. DYNAMAX PREMIUM ULTRA LE 5W/30 is developed for use in engine which are equipped with or without an exhaust gas after treatment system.

Specification:

SAE 5W/30
API SN/CF, ACEA C3

Approvals:

MB-Approval 229.51, BMW LL-04
RN700

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	11,7
Kinematic viscosity at 40°C, mm ² /s	typical value	65
Viscosity index	min.	175
Density at 15°C, kg/m ³	typical value	850
Pour point, °C	max.	- 39
Flash point (COC), °C	min.	218

Specification variations in these characteristics may occur. Further informations to be available by SDS.