

TECHNICAL DATA SHEET

Date issued: 04.04.2017

DYNAMAX AIRCO CLEANER spray

1. Description

This technical sheet is valid for production, testing and delivery of DYNAMAX A/C CLEANER spray. DYNAMAX A/C CLEANER spray is used to cleaning to condition the air-conditioning in motor vehicles.

Characteristics:

High quality cleansing foam to condition the air-conditioning in motor vehicles. Effective cleaning foam. Subtle scent. Optimizes the functioning of the air-conditioning. Prevents malfunction.

Physical state:

DYNAMAX A/C CLEANER spray is a white foam with a characteristic odour.

Application:

DYNAMAX A/C CLEANER should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Before treatment, switch off the engine and the electrical installations. Apply the foam to the condenser of the air conditioning by means of the enclosed adapter. Insert the adapter about 30 centimetres into the air inlet of the air conditioning and completely empty the can. The location of the air inlet differs per brand, consult your dealer. After applying, do not switch on the engine or the electrical installations for at least half an hour. In this half hour the foam will break and leave the system through the condensed water outlet as a fluid.

2. Technical parameters

DYNAMAX A/C CLEANER must comply with the following specifications:

Physical state	foam
Colour	white
Odour	mint - menthol
рН	10 - 11
Density at 20°C [g/cm ³]	$0,967 \pm 0,010$
VOC – content [obj.%]	min. 27
Vapour pressure at 20°C [bar]	-
Refractive Index at 25°C	-
Flash Point [°C]	< 21
Hazard symbols	UN 1950, class 2 5F Gases

Contains:

- 15% - 30% aliphatic hydrocarbons



TECHNICAL DATA SHEET

Date issued: 04.04.2017

4. Fire-fighting properties: Combustible of I. hazard degree.

5. Delivery:
All matters concerned delivery and transportation of the product DYNAMAX A/C CLEANER are the object of a purchase contract, but must be in accordance with these regulations.

Contact address:

EURO-VAT, Ltd. 951 22 Alekšince 231 Slovak Republic tel./fax: 00421/37 78 22 326-7

e-mail: eurovat@eurovat.sk www.dynamaxoil.com