

TECHNICAL DATA SHEET

Date issued: 01.03.2017

DYNAMAX CARBURETOR CLEANER SPRAY

1. Description

This technical sheet is valid for production, testing and delivery of DYNAMAX CARBURETOR CLEANER – spray. DYNAMAX CARBURETOR CLEANER is used to cleaning the carburettors.

Characteristics:

High quality cleaner for the interior and the exterior of carburettors and valves, without disassembly. High dissolving properties. Leaves no residue. Non-corrosive.

Physical state:

DYNAMAX CARBURETOR CLEANER is a colourless aerosol with a characteristic odour.

Application:

DYNAMAX CARBURETOR CLEANER should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Switch of the engine and allow to cool down. Remove the air filter. Spray the exterior of the carburettor until the contamination has disappeared. Spray the visible parts of the interior of the carburettor and allow to take effect. Start the engine and let idle with very limited speed. Spray the carburettor cleaner several times at the air inlet and increase the speed of the engine. Switch the engine off and install the air filter.

2. Technical parameters

DYNAMAX CARBURETOR CLEANER must comply with the following specifications:

Physical state	aerosol
Colour	colourless
Odour	characteristic
рН	neutral
Density at 20°C [g/cm ³]	0.840 ± 0.010
VOC – content [obj.%]	100
Vapour pressure at 20°C [bar]	3 – 4
Refractive Index at 25°C	-
Flash Point [°C]	< 21
Hazard symbols	UN 1950, class 2 5F Gases

Contains:

hydrocarbons



TECHNICAL DATA SHEET

Date issued: 01.03.2017

4. Fire-fighting properties: Combustible of I. hazard degree.

object of a purchase contract, but must be in accordance with these regulations.

Contact address:

EURO-VAT, Ltd. 951 22 Alekšince 231 Slovak Republic

tel./fax: 00421/37 78 22 326-7 e-mail: eurovat@eurovat.sk

www.eurovat.sk, www.dynamaxoil.com