



TECHNICAL DATA SHEET

Date issued: 12.11.2017

DYNAMAX CONTACT SPRAY

1. Description

This technical sheet is valid for production, testing and delivery of DYNAMAX CONTACT SPRAY. DYNAMAX CONTACT SPRAY is designed to cleaning the electrical contacts.

Characteristics:

High quality spray to clean electrical contacts. Powerful jetspray. High dissolving properties. Leaves no residue. Non- conductive. Non-corrosive.

Physical state:

DYNAMAX CONTACT SPRAY is a colourless aerosol with a characteristic odour.

Application:

DYNAMAX CONTACT SPRAY should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Switch off electrical installations before treatment. Spray the parts to be treated until the contamination has disappeared. Contaminated contact cleaner should be regarded as chemical waste. Only switch on the electrical installation after evaporation of the solvent (minimum of 15 minutes).

2. Technical parameters

DYNAMAX CONTACT SPRAY must comply with the following specifications:

Physical state	aerosol
Colour	colourless
Odour	characteristic
Density at 20°C [g/cm³]	0,663 ± 0,010
VOC – content [obj. %]	min. 84,3
Vapour pressure at 20°C [bar]	5,5 – 6,5
Refractive Index at 25°C	1,370
Flash Point [°C]	< 0

Contains:

- more than 30% aliphatic hydrocarbons



EURO-VAT, s.r.o
951 22 Alekšince 231
tel/fax: 037/ 782 23 26-7
www.eurovat.sk

2/2

TECHNICAL DATA SHEET

Date issued: 12.11.2017

3. Storage and shelf life:

Store it in tightly-closed containers in a dry and well-ventilated store room at the temperature up to +40 °C .

4. Fire-fighting properties:

Combustible of I. hazard degree.

5. Delivery:

All matters concerned delivery and transportation of the product DYNAMAX SPRAY are the object of a purchase contract , but must be in accordance with these regulations.

Contact address:

EURO-VAT, Ltd.
951 22 Alekšince 231
Slovak Republic
tel./fax: 00421/37 78 22 326-7
e-mail: eurovat@eurovat.sk
www.eurovat.sk, www.dynamaxoil.com