

TECHNICAL DATA SHEET

Date issued: 01.03.2017

DYNAMAX EGR CLEANER spray

1. Description

This technical sheet is valid for production, testing and delivery of DYNAMAX EGR CLEANER spray. DYNAMAX EGR CLEANER spray is used to dissolve deposits in EGR valve.

Characteristics:

DYNAMAX EGR CLEANER spray is used to dissolve deposits in EGR valve, air intake system, manifold and inlet valves. To restore air flow to engine, improving power and acceleration and reducing exhaust smoke.

Physical state:

DYNAMAX EGR CLEANER spray is a colorless aerosol with a characteristic odour.

Application:

DYNAMAX EGR CLEANER spray observe the instructions of the car manufacturer. For professional use only. Loosen the hose between turbo and air intake system. Start engine and allow to run at approx. 2000 rpm. Spray directly into inlet of manifold by repeatedly, briefly pressing the nozzle till the engine runs more smoothly. Install the hose.

2. Technical parameters

DYNAMAX EGR CLEANER spray must comply with the following specifications:

Physical state	aerosol
Colour	colorless
Odour	characteristic
рН	neutral
Density at 20°C [g/cm ³]	$0,727 \pm 0,010$
VOC – content [obj.%]	100
Vapour pressure at 20°C [bar]	-
Refractive Index at 25°C	-
Flash Point [°C]	< 21
Hazard symbols	UN 1950, class 2 5F Gases

Contains:

- >= 30% aliphatic hydrocarbons, 15 - 30% aromatic hydrocarbons



TECHNICAL DATA SHEET

Date issued: 01.03.2017

4. Fire-fighting properties: Combustible of I. hazard degree.

5. Delivery:

All matters concerned delivery and transportation of the product DYNAMAX EGR CLEANER spray are the object of a purchase contract, but must be in accordance with these regulations.

Contact address:

EURO-VAT, Ltd. 951 22 Alekšince 231 Slovak Republic

tel./fax: 00421/37 78 22 326-7 e-mail: eurovat@eurovat.sk www.dynamaxoil.com