

TECHNICAL DATA SHEET

Date issued: 04.12.2017

DYNAMAX MULTI FOAM spray

1. Description

This technical sheet is valid for production, testing and delivery of DYNAMAX MULTI FOAM spray. DYNAMAX MULTI FOAM is used to clean the interior.

Characteristics:

High quality, universal cleaning foam for light contaminations. DYNAMAX MULTI FOAM is designed to clean the interior houses, cars. Removes sediment smoke, paints or lubricants. Dissolves very well, has a pleasant smell.

Physical state:

DYNAMAX MULTI FOAM is a white foam with a characteristic odour.

Application:

DYNAMAX MULTI FOAM should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Apply DYNAMAX MULTI FOAM and allow to take effect. Remove the dirt with a dry, clean cloth.

2. Technical parameters

DYNAMAX MULTI FOAM must comply with the following specifications:

Physical state	foam
Colour	white
Odour	characteristic
Density at 20°C [g/cm ³]	$0,960 \pm 0,010$
VOC – content [obj.%]	25
pН	9,5 – 10,5
Vapour pressure [bar]	3 - 4
Flash Point [°C]	< 0

Contains:

- aliphatic hydrocarbons 5-15%



TECHNICAL DATA SHEET

Date issued: 04.12.2017

4. Fire-fighting properties: Combustible of I. hazard degree.

<u>5. Delivery:</u> All matters concerned delivery and transportation of the product DYNAMAX MULTI FOAM are the object of a purchase contract, but must be in accordance with these regulations.

Contact address:

EURO-VAT, Ltd. 951 22 Alekšince 231 Slovak Republic tel./fax: 00421/37 78 22 326-7 e-mail: eurovat@eurovat.sk

www.eurovat.sk, www.dynamaxoil.com