



TECHNICAL DATA SHEET

Date issued: 01.03.2017

DYNAMAX PENETRATION OIL SPRAY

1. Description

This technical sheet is valid for production, testing and delivery of DYNAMAX PENETRATION OIL – spray. DYNAMAX PENETRATION OIL is designed to loosen rusted parts.

Characteristics:

High quality effective tool to loosen rusted parts. Good penetrating properties. Contains graphite and MoS₂. Moisture repellent. Rust preventive. Can be used in various positions. Powerful jetspray.

Physical state:

DYNAMAX PENETRATION OIL is a colourless aerosol with a characteristic odour.

Application:

DYNAMAX PENETRATION OIL should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Apply the penetrating oil and allow it to take effect.

2. Technical parameters

DYNAMAX PENETRATION OIL must comply with the following specifications:

Physical state	aerosol
Colour	colourless
Odour	characteristic
pH	neutral
Density at 20°C [g/cm³]	0,860 ± 0,010
VOC – content [obj.%]	min. 70
Vapour pressure at 20°C [bar]	3 – 4
Refractive Index at 25°C	-
Flash Point [°C]	< 0
Hazard symbols	UN 1950, class 2 5F Gases

Contains:

-



EURO-VAT, s.r.o
951 22 Alekšince 231
tel/fax: 037/ 782 23 26-7
www.eurovat.sk

2/2

TECHNICAL DATA SHEET

Date issued: 01.03.2017

3. Storage and shelf life:

Store it in tightly-closed containers in a dry and well-ventilated store room at the temperature up to +40 °C .

4. Fire-fighting properties:

Combustible of I. hazard degree.

5. Delivery:

All matters concerned delivery and transportation of the product DYNAMAX PENETRATION OIL are the object of a purchase contract , but must be in accordance with these regulations.

Contact address:

EURO-VAT, Ltd.
951 22 Alekšince 231
Slovak Republic
tel./fax: 00421/37 78 22 326-7
e-mail: eurovat@eurovat.sk
www.eurovat.sk, www.dynamaxoil.com