

TECHNICAL DATA SHEET

Date issued: 17.10.2017

DYNAMAX POLISH & WAX

1. Description

This technical sheet is valid for production ,testing and delivery of DYNAMAX POLISH & WAX. DYNAMAX POLISH & WAX is designed for polish.

Characteristics:

DYNAMAX POLISH & WAX is a combination of polishing paste with medium polishing effect and paint protection with excellent and streak-free depth gloss. Polish and wax can be used on all types of paint. It removes small and medium scratches and seals the paint without streaks for several weeks. Polish and wax can be processed very simply, quickly and easy by hand or with machine.

Physical state:

DYNAMAX POLISH & WAX is a viscous fluid of yellow colour.

Application:

DYNAMAX POLISH & WAX apply some polish wax on a sponge or a polishing cloth and polish in circular movements on partial surfaces of approx. 0,5 - 1 m² - then polish with a clean and dry cloth. Change the cloth frequently. Repeat the procedure until the complete vehicle is sealed. Before it begins. The vehicle should be clean and washed. The application can be applied on dry or slightly damp varnish. The paint should not be too hot and the car should not stand in the blazing sun.

2. Technical parameters

DYNAMAX POLISH & WAX must comply with the following specifications:

Physical state	viscous fluid
Colour	yellow
Odour	distinctive perfume odour
Density at 20°C [g/cm ³]	$0,980 \pm 0,010$
pН	8
Flash Point [°C]	> 65
Hazard symbols	-



TECHNICAL DATA SHEET

Date issued: 17.10.2017

4. Fire-fighting properties:

DYNAMAX POLISH & WAX is not combustible.

5. Delivery:

All matters concerned delivery and transportation of the product DYNAMAX POLISH & WAX are the object of a purchase contract, but must be in accordance with these regulations.

Contact address:

EURO-VAT, Ltd. 951 22 Alekšince 231 Slovak Republic

tel./fax: 00421/37 78 22 326-7 e-mail: eurovat@eurovat.sk

www.eurovat.sk, www.dynamaxoil.com