



TECHNICAL DATA SHEET

Date issued: 04.10.2020

DYNAMAX HYPOL 75W/85 GL-5

1. Product description:

DYNAMAX HYPOL 75W/85 GL-5 - is based on special selected high-performance synthetic base oil. It contains package of additives which improves extreme pressure resistance, excellent thermal and oxidation stability, low pour point, saving fuel consumption, excellent protection against the foaming, corrosion and wear.

Properties:

- Excellent viscosity-temperature behavior
- Minimal wear
- Excellent extreme pressure properties
- Prevention of foam generation
- Excellent limited slip properties
- Neutral behavior towards metal and sealing materials

Use:

DYNAMAX HYPOL 75W/85 GL-5 - is universal high-performance transmission oil for use in CVT transmissions, manual transmission of the modern passenger car and light commercial vehicles where an API GL-5 is recommended.

Specification:

API GL-5

Approvals:

- MIL-L2105E; API MT-1, SAE J2360; VW TL 521 45-X (G 052 145 A1);
VW TL 521 90 (G 052 190 A2/ G 055 190 A2), MB 235.7, MB 235.74,
MB 239.71, MB 239.72, ZF TE-ML 18

2. Technical parameters:

Kinematic viscosity at 100°C, mm ² /s	typical value	11,6
Kinematic viscosity at 40°C, mm ² /s	typical value	64,3
Viscosity index	min.	177
Density at 15°C, kg/m ³	typical value	865
Pour point, °C	max.	- 54
Flash point (COC), °C	min.	218

Specification variations in these characteristics may occur. Further informations to be available by SDS.