



## TECHNICAL DATA SHEET

Date issued: 24.03.2021

# DYNAMAX COOL ULTRA G12 -8

### **1. Product description:**

DYNAMAX COOL ULTRA G12 -8 is a cooling liquid based on ethylene glycol. It is designed to coolers of modern aluminium and cast-iron cooling systems of combustion engines. DYNAMAX COOL ULTRA G12 -8 protects the car year-round cooling system from the action of frost and corrosion. It provides very good heat transfer. Includes high-inhibitors corrosion protection for cooling system. Meets VW TL 774 D-F.

#### Use:

DYNAMAX COOL ULTRA G12 -8 is used for cooling systems for internal combustion engines. DYNAMAX COOL ULTRA G12 -8 serves as a full replacement for the coolant, which are made based on 1,2 - ethylene glycol (or glycol). Compatible with metal materials. Application: Undiluted pour into the radiator system. Painted surfaces should be sprayed with water after.

### **2. Technical parameters:**

Physical state	liquid
Colour	green
Odour	odorless
Freezing point, °C	- 8 +/- 1°C
Density at 20°C, kg/m <sup>3</sup>	1,030 - 1,040
Solubility in water, g.l <sup>-1</sup>	soluble
Solubility in solvents, g.l <sup>-1</sup>	alcohol, ether

Specification variations in these characteristics may occur. Further informations to be available by SDS.