

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Creation date

02nd June 2022

Revision date

Version

1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Substance / mixture

mixture

UFI

WGMX-UE9N-Q107-PSX3

Other mixture names

DYNAMAX ALL-SEASON DIESEL ADDITIVE

1.2. Relevant identified uses of the substance or mixture and uses advised against**Mixture's intended use**

the product ensures the improvement of the flow properties of diesel fuel

Secondary uses

PC-FUE-5

Fuel additives and fuel components

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet**Supplier**

Name or trade name

EURO-VAT spol. s r.o.

Address

Alešince 231, Alešince, 951 22

Slovakia

Identification number (CRN)

18049397

VAT Reg No

SK2020408808

Phone

037/78 22 326

E-mail

eurovat@eurovat.sk

Web address

www.dynamaxoil.com

Competent person responsible for the safety data sheet

Name

EURO-VAT spol. s r.o.

E-mail

eurovat@eurovat.sk

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Flam. Liq. 3, H226

Asp. Tox. 1, H304

STOT SE 3, H335, H336

Aquatic Chronic 2, H411

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Hazard pictogram****Signal word**

Danger

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Creation date

02nd June 2022

Revision date

Version

1.0

Hazardous substances

hydrocarbons, C9, aromatics

Hazard statements

H226

Flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H335

May cause respiratory irritation.

H336

May cause drowsiness or dizziness.

H411

Toxic to aquatic life with long lasting effects.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310

IF SWALLOWED: Immediately call a doctor.

P331

Do NOT induce vomiting.

P501

Dispose of contents/container to a hazardous waste in accordance with relevant legislation.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 64742-95-6 Registration number: 01-2119455851-35-xxxx	hydrocarbons, C9, aromatics	40-70	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335, H336 Aquatic Chronic 2, H411	
Index: 601-052-00-2 CAS: 91-20-3 EC: 202-049-5 Registration number: 01-2119513401-57-xxxx	naphthalene	0,4-0,8	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	1
Index: 601-043-00-3 CAS: 95-63-6 EC: 202-436-9 Registration number: 01-2119472135-42-xxxx	1,2,4-trimethylbenzene	0,1-1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Chronic 2, H411	1

Notes

1 Substance with a Union workplace exposure limit.

Full text of all classifications and hazard statements is given in the section 16.

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Creation date

02nd June 2022

Revision date

Version

1.0

SECTION 4: First aid measures**4.1. Description of first aid measures**

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

Cough, headache. May cause respiratory irritation. May cause drowsiness or dizziness.

If on skin

Not expected.

If in eyes

Not expected.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray.

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Creation date

02nd June 2022

Revision date

Version

1.0

6.2. Environmental precautions

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. No smoking. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

The mixture contains substances for which occupational exposure limits are set.

European Union**Commission Directive 2000/39/EC**

Substance name (component)	Type	Value
1,2,4-trimethylbenzene (CAS: 95-63-6)	OEL 8 hours	100 mg/m ³
	OEL 8 hours	20 ppm

European Union**Commission Directive 91/322/EEC**

Substance name (component)	Type	Value
naphthalene (CAS: 91-20-3)	OEL 8 hours	50 mg/m ³
	OEL 8 hours	10 ppm

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

It is not needed.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Contaminated skin should be washed thoroughly.

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Creation date	02nd June 2022	Version	1.0
Revision date			

Respiratory protection

Mask with a filter against organic vapours in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	160-230 °C
Flammability	Flammable liquid and vapour.
Lower and upper explosion limit	
bottom	0,6 %
upper	7 %
Flash point	>59 °C
Auto-ignition temperature	240 °C
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	insoluble
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	100 kPa
Density and/or relative density	
Density	0,860-0,880 g/cm ³ at 20 °C
Form	liquid

9.2. Other information

Evaporation rate	data not available
------------------	--------------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Creation date

02nd June 2022

Revision date

Version

1.0

Acute toxicity

Based on available data the classification criteria are not met.

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Based on available data the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

not available

SECTION 12: Ecological information**12.1. Toxicity****Acute toxicity**

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

not available

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Creation date

02nd June 2022

Revision date

Version

1.0

Waste type code

13 07 03 other fuels (including mixtures) *

15 01 10 packaging containing residues of or contaminated by hazardous substances *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information**14.1. UN number or ID number**

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III - substances presenting low danger

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

UN number

Classification code

Safety signs

30**1993**

F1

3+hazardous for the environment

**Marine transport - IMDG**

EmS (emergency plan)

MFAG

F-E, S-E

310

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Creation date	02nd June 2022	Version	1.0
Revision date			

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P301+P310	IF SWALLOWED: Immediately call a doctor.
P331	Do NOT induce vomiting.
P501	Dispose of contents/container to a hazardous waste in accordance with relevant legislation.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EÚ	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
log Kow	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution from Ships
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

DYNAMAX CELOROČNÉ ADITÍVUM DO NAFTY 1:1000

Creation date	02nd June 2022	Version	1.0
Revision date			

Asp. Tox.	Aspiration hazard
Carc.	Carcinogenicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.