



## TECHNICAL DATA SHEET

# DYNAMAX ALL-SEASON DIESEL ADDITIVE

Date issued: 13.10.2021

### 1. Description

DYNAMAX ALL-SEASON DIESEL ADDITIVE – ensures improved flow properties of all diesel fuels and is suitable for use in all diesel aggregates with or without diesel particulate filter. Winter safe down to -25°C (depending on the fuel quality). Reliably prevents from formation of paraffin crystals at low temperatures.

#### Application:

Add regularly during the winter months before start of the frost periods to the tank before filling up. DYNAMAX ALL-SEASON DIESEL ADDITIVE shall be used before gelling of the diesel fuel at approx. 0°C fuel temperature respectively during fillip up the diesel tank.

Application ratio 1:1000 (60 ml sufficient for 60 L diesel fuel). Product works during operation.

Also suitable for stationary diesel engines.

Advice: Store under frost-free conditions! Shake well before use!

#### Benefits:

Optimal flow properties of the diesel fuel ensure optimal operation of all system components and safe driving conditions. Easy application. Provides for a safe operation of diesel aggregates in winter and in summer periods. Maintains the flow properties of the fuel. Improves the filterability of the diesel fuel and prevents from blocking of the fuel filter. Ensures improved cold start properties in the winter period.

**Application field:** all diesel engines

**Consumption:** 60 ml for 60 l diesel // concentrate 1:1000

**Application interval:** on demand

### 2. Technical parameters

DYNAMAX ALL-SEASON DIESEL ADDITIVE must comply with the following specifications:

<b>Physical state</b>	liquid
<b>Colour</b>	colourless
<b>Odour</b>	characteristic
<b>Relative density [g.cm<sup>-3</sup>]</b>	0,860 – 0,880
<b>Boiling Point [°C]</b>	160 - 230
<b>Flash Point [°C]</b>	>59

Specification variations in these characteristics may occur. Further informations to be available by SDS.