



TECHNICAL DATA SHEET

DYNAMAX GASOLINE ADDITIVE E10

Date issued: 28.02.2022

1. Description

DYNAMAX GASOLINE ADDITIVE E10 – highly effective package of active substances that suppress the negative properties of gasoline E10 and E5 fuels with increased content of bio-components. Stabilizes the ethanol and binds water to itself, thus preventing the formation of condensation and corrosion in the fuel system and at the same time prolongs the life of the fuel itself. Improves combustion and the lubricity of biofuels. Prevents sediments and separation of the bio-components.

Application:

Pour 50 ml per 50 l of petrol into the fuel tank before each refueling.

Benefits:

- Eliminates negative effects of E10 and E5 gasoline
- Binds moisture and prevents formation of condensation in the fuel system
- Suitable for all 2- and 4-stroke gasoline engines
- Prevents corrosion, formation of deposits
- Compatible with turbochargers and catalytic converters
- Prolongs fuel life
- Improves the combustion and lubricity of biofuels

Application field: gasoline engines

Consumption: 50 ml for 50 l of gasoline // concentrate 1:1000

Application interval: on demand

2. Technical parameters

DYNAMAX GASOLINE ADDITIVE E10 must comply with the following specifications:

Physical state	liquid
Colour	orange
Odour	characteristic
Relative density [g.cm⁻³]	0,750 – 0,850
Boiling Point [°C]	82
Flash Point [°C]	12

Specification variations in these characteristics may occur. Further informations to be available by SDS.